

PONTO



IP 67

IK 10



MAIN APPLICATIONS



SQUARES & PEDESTRIAN AREAS



RAILWAY STATIONS & METROS



ACCENT & ARCHITECTURAL

Various
monochromatic
static versions
for illumination
and ground
lighting

PONTO is a recessed LED floodlight.

It provides a range of light distributions for a variety of solutions including lighting architectural elements or ground-lighting public or private areas.

The synthetic body, which houses the optical compartment, is reinforced with fibre glass and has a stainless steel finishing frame. The power supply is fitted in the body.

The 12-mm tempered-glass protector, with its high mechanical resistance, can withstand a static load of 2,000kg. Thanks to these different elements of mechanical design, the luminaire's IP 67 tightness level is maintained in the long term.

KEY ADVANTAGES


- > Illumination or ground-lighting version
- > Different installation possibilities, with or without a kit
- > Extra-high tightness (IP 67)
- > Available with clear or frosted glass (option)
- > High-quality and resistant materials

PONTO

Typical luminaire output flux (white LEDs)	160 to 330lm
Power consumption	5W
Colour temperature	Warm white 830, neutral white 740, cool white 757, static amber, red, green or blue LEDs
Light distributions	Symmetrical (10°-12°-20°-22°-26°-36°-38°-40°) beams
Nominal voltage	220-240V / 50-60Hz
Surge protection	10kV



DIMENSIONS

PONTO	
A	110mm 4.3"
B	110mm 4.3"
C	70mm 2.7"
 KG	0,45kg 1lbs

